

AD-A061 474

ADVISORY GROUP FOR AEROSPACE RESEARCH AND DEVELOPMENT--ETC F/G 20/4
TECHNICAL EVALUATION REPORT ON THE FLUID DYNAMICS PANEL SYMPOSI--ETC(U)
OCT 78 H BERGH

UNCLASSIFIED

AGARD-AR-128

NL

1 OF 1
AD
A061474



END
DATE
FILMED
1-79
DDC

ADA061474

AGARD-AR-128

DDC FILE COPY

LEVEL
AGARD-AR-128

AGARD

ADVISORY GROUP FOR AEROSPACE RESEARCH & DEVELOPMENT

7 RUE ANCELLE 92200 NEUILLY SUR SEINE FRANCE

AGARD ADVISORY REPORT No. 128

Technical Evaluation Report
on the

Fluid Dynamics Panel

Symposium on

Unsteady Aerodynamics

by

H. Bergh

DDC

NOV 24 1978

A

NORTH ATLANTIC TREATY ORGANIZATION



DISTRIBUTION AND AVAILABILITY
ON BACK COVER

DISTRIBUTION STATEMENT A

Approved for public release
Distribution Unlimited

78 11 17 08

NORTH ATLANTIC TREATY ORGANIZATION
ADVISORY GROUP FOR AEROSPACE RESEARCH AND DEVELOPMENT
(ORGANIZATION DU TRAITE DE L'ATLANTIQUE NORD)

9
AGARD Advisory Report No. 128

6
TECHNICAL EVALUATION REPORT
on the
FLUID DYNAMICS PANEL SYMPOSIUM
on
UNSTEADY AERODYNAMICS

by

10
H/Bergh
National Aerospace Laboratory (NLR)
Anthony Fokkerweg 2
1059 CM Amsterdam
The Netherlands

12

11p.

11

Oct 78

CONTENTS

	Page
1. INTRODUCTION	1
2. GENERAL OVERVIEW	1
3. CRITICAL COMMENTS	2
4. CONCLUSIONS AND RECOMMENDATIONS	3
5. REFERENCES - CONFERENCE PAPERS	3

400 043

507

The Proceedings of the AGARD Fluid Dynamics Panel Symposium on Unsteady Aerodynamics, which was held in Ottawa on 26-28 September 1977, are published as AGARD-CP-227, February 1978.

78 11 17 08 1

THE MISSION OF AGARD

The mission of AGARD is to bring together the leading personalities of the NATO nations in the fields of science and technology relating to aerospace for the following purposes:

- Exchanging of scientific and technical information;
- Continuously stimulating advances in the aerospace sciences relevant to strengthening the common defence posture;
- Improving the co-operation among member nations in aerospace research and development;
- Providing scientific and technical advice and assistance to the North Atlantic Military Committee in the field of aerospace research and development;
- Rendering scientific and technical assistance, as requested, to other NATO bodies and to member nations in connection with research and development problems in the aerospace field;
- Providing assistance to member nations for the purpose of increasing their scientific and technical potential;
- Recommending effective ways for the member nations to use their research and development capabilities for the common benefit of the NATO community.

The highest authority within AGARD is the National Delegates Board consisting of officially appointed senior representatives from each member nation. The mission of AGARD is carried out through the Panels which are composed of experts appointed by the National Delegates, the Consultant and Exchange Programme and the Aerospace Applications Studies Programme. The results of AGARD work are reported to the member nations and the NATO Authorities through the AGARD series of publications of which this is one.

Participation in AGARD activities is by invitation only and is normally limited to citizens of the NATO nations.

The content of this publication has been reproduced directly from material supplied by AGARD or the author.

AGARD REF	
RTA	Write Section <input checked="" type="checkbox"/>
ODS	Write Section <input type="checkbox"/>
UNCLASSIFIED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	AVAIL. CODE or SPECIAL
A	

Published October 1978

Copyright © AGARD 1978

All Rights Reserved

ISBN 92-835-1300-2



Printed by Technical Editing and Reproduction Ltd
Harford House, 7-9 Charlotte St, London, W1P 1HD

TECHNICAL EVALUATION REPORT ON THE AGARD FLUID DYNAMICS PANEL SYMPOSIUM ON UNSTEADY AERODYNAMICS

by

H. Bergh
National Aerospace Laboratory NLR
Anthony Fokkerweg 2
1059 CM AMSTERDAM
THE NETHERLANDS

1. INTRODUCTION

From 26-28 September 1977 the Fluid Dynamics Panel of AGARD arranged a Symposium on "Unsteady Aerodynamics" at the Government Conference Centre, Ottawa, Canada. This Symposium was organized by an international Programme Committee headed by Prof. A.D. Young, who also chaired the Round Table Discussion.

The programme consisted of the following 5 sessions:

- I Unsteady Subsonic and Supersonic Flow
- II Unsteady Transonic Flow
- III Unsteady Non-Separated and Separated Boundary Layers
- IV Viscous-Inviscid Interactions, Dynamic Stall
- V Unsteady Flows Associated with Rotors, Cascades and Turbo Machinery.

These 35 papers and the Round Table Discussions are published in AGARD Conference Proceeding No. 227, "Unsteady Aerodynamics".

As the proceedings are already available the evaluator has refrained from a detailed review of the lectures and has restricted his task to an attempt to sketch the main developments in each field to which a session was devoted, to consider their mutual relations and to present conclusions and recommendations.

The views expressed are the sole responsibility of the evaluator.

2. GENERAL OVERVIEW

The various items of research conducted in a certain field may be considered as ships on a river. All ships are sailing from the origin of "basic research" through passages called "increasing knowledge", "attempt of modeling", "development and testing of prediction methods" to the wide sea of "practical application". The various stages of development are revealed by a time exposure as different positions of the ships on the river. As a symposium provides us with such a time exposure, we may evaluate the present situation in "Unsteady Aerodynamics" on the basis of our symposium.

At a first glance, we see distinct differences in the positions on the river, not only between the research ships of one problem fleet, but also between the various problem fleets. Looking more closely, it becomes evident that the ships belonging to session I "Unsteady subsonic and supersonic flow" are sailing ahead on our river, while some ships already seem to have reached the sea. For these speed regimes our knowledge about the aerodynamic forces acting on harmonically oscillating surfaces in inviscid attached flow is certainly well developed 1, 3, 5, 9.

In his review paper 1 Ashley considered also the capability of linearized theory for harmonically oscillating lifting surfaces, slender bodies and interfering configurations. He warned against further refinement of the linearized tools ("misplaced efforts") and pointed to possibilities for calculating small but arbitrary motions. In this respect he believed that Edwards' work will provide a sound basis for modifying existing prediction methods for harmonic motions. A future goal he sketched his dream of a unified computational fluid dynamics for steady and unsteady 3-D flows, capable to predict accurate results for various types of motions of practical configurations in all speed regimes.

In an attempt to bring this future to the present, Morino and Tseng 3 marched in with SOUSSA, a computer program for Steady Oscillatory and Unsteady, Subsonic and Supersonic Aerodynamics. Recent improvements were reported together with some results. An interesting question is whether such a general computer program with its continuous adaption process to latest developments is sufficiently flexible in application to compete with more pragmatic approaches. A good example of the latter was presented by Roos et al., 9 who verified the applicability of their NLRI method on a complete aircraft with external stores. For such a configuration calculated flutter characteristics were shown to be in good agreement with flutter tests in a wind tunnel and in free flight.

Another experimental check on the validity of linearization, at least for incompressible flow, was given by Patel 4 who measured lift and pitching moment on two finite model wings in vertical gusts. The aerodynamic force response to gusts with two harmonic frequency components were shown to be in close agreement with a superposition of corresponding responses to single components.

This satisfactory situation existing in subsonic and supersonic flow applies only for attached flow. As soon as we are dealing with separated flows, our theoretical means fail in practical situations and our wind tunnel experiments may suffer seriously from limitations in Reynolds number. There is one exception. Wings with leading edge separation (in steady and unsteady flows) can be treated quite well with a nonlinear discrete vortex method, as was shown by Kandil 2 et al. Their general method, not restricted to small or harmonic motions, was applied to delta wings and gave good agreement with experimental results.

As could be expected from the greater complexity of their problems, the ships of session II "Unsteady transonic flow" are lagging far behind those of the previous session. But driven by the strong need for safety of a new generation of aircraft and stimulated by increased physical understanding 10, some ships seem to be steering a good course. In this problem area the experimental work, mainly devoted to two-dimensional attached flow, has played a guiding part. Our physical understanding of shockwave behaviour and of the strong influence of the steady flow field on unsteady aerodynamics was improved considerably by Tijdemans' experiments directed to special flow features 10. Additional contributions were presented during the Symposium 8, 13.

In recent years prediction methods for 2-D flow have achieved impressive results. A good example is presented at this Symposium by Yoshihara et al 14, showing the potential of such methods for aeroelastic

optimization purposes. However, it is a pity that the calculation method was not used to study the applicability of superposition in this speed range. As recent physical observations stressed the importance of shock wave motions, it is not surprising that this phenomenon got much attention in newly proposed calculation methods. An efficient procedure for handling shock wave motion in 2-D flow was demonstrated by Seebass et al.¹¹. This shock-wave treatment was also discussed extensively in the promising considerations of Liu and Winther¹² about a mixed kernel function approach for 3-D flow. However, as was stressed by Tijdeman in his review lecture¹⁰, the viscous effects are very important in this speed regime. So there is a strong need for blending the present calculation methods for inviscid flow with some engineering type method that accounts for the main viscous effects.

Looking again at our river, far behind the transonic vessels we see the unsteady boundary layer vessels and the ships dealing with viscous-inviscid interactions near stall conditions. Both groups, guided by helicopters, clearly are sailing in close contact. Yet the research on unsteady turbulent boundary layers seems to lose forward speed in spite of many investigations. As Telionis¹⁶ stated: "Successful modeling of the turbulent boundary layer is a clear challenge to the theoreticians. They will have to invent new models that would take into account the interaction between the organized fluctuations of the outer flow and the random fluctuations of turbulence". Although a certain picture emerges from the experimental evidence, there still remains a strong need for detailed, accurate experimental data with well documented initial conditions. A good example of careful experiments was shown in the contribution of the ONERA group¹⁷. Their continuous effort gradually discloses more details of the turbulent boundary layer and leads to a better physical insight.

The research on the dynamic stall problem has developed rather rapidly in the last decade. Careful experiments have revealed many details of the phenomena occurring during the stall process. Attempts to understand the mechanism and even to model it had some success as long as only the NACA 0012 section was considered. However, as Philippe²¹ illustrated in his review paper, stall may be introduced by various causes, depending on several known and unknown circumstances. His conclusions that dynamic stall is still too complex to be understood sufficiently even in the simple case of 2-D airfoils, while at the same time it is questionable whether 2-D observations are useful in 3-D cases, were shared by a large part of the audience.

The contributions 23, 24, 26 concerning numerical solutions of the Navier-Stokes equations did not change the overall view. Impressive results were presented about the flow around airfoils, roughly showing similar features as observed in the experiments of Saxena et al.²² and Dymant and Gryson²⁸. However, as the calculations cover only low Reynolds number (up to 104), it remains doubtful whether this way of attack may provide us with useful information for practical applications on helicopters or fixed wing aircraft.

The important field of unsteady flows associated with rotors, cascades and turbo machinery was not covered so well. The two review lectures, one by Byham and Beddoes on unsteady rotor aerodynamics³² and the other by Platzer on unsteady flows in turbo machines³³, are both excellent surveys of the fields considered but did not get the deserved response, probably due to the limited number of associated contributions. This rather isolated position was emphasized also by the fact, that these subjects were not touched on during the R.T.D. A specialists meeting seems to be better suited for these subjects.

3 CRITICAL COMMENTS

It is not surprising that large differences in development are observed between the various subjects in unsteady aerodynamics, since in general, progress in research depends on two counteracting factors: the need for a solution and the complexity of the problem. The former determines the will to spend money or manpower, the latter is a measure of the severity of the struggle laying ahead. So the various stages in development attained are no more than a result of the weighting factors of the needs and the complexities of the various problems. However, a point of concern is the apparent lack of communication between the groups. This stems from the historical development that has gone in an application oriented way: either fixed wing aircraft research or helicopter research. For subsonic and supersonic flutter investigations of fixed wing aircraft unsteady aerodynamics assuming inviscid attached flow appeared to be sufficient. For helicopter rotors, however, operating locally around stall conditions, strong interactions between the inviscid outer flow and the separated or non-separated boundary layer regions exist. As the fixed wing people did not display any interest in viscous phenomena, it is natural that unsteady boundary layer research was devoted almost explicitly to problems associated with rotor aerodynamics. To reduce the complexity of the 3-D flow problem near the stall, many studies are dealing with 2-D situations only. This historical development along different lines was reflected also in the programme set up of our Symposium.

However, there are some signs which can be regarded as forerunners of another situation. For example viscous effects are playing an important role in unsteady high subsonic and transonic aerodynamics, not only with regard to flutter aerodynamics but also in the unsteady off-design behaviour (buffeting) of advanced wings, a topic that was not touched upon during the Symposium presentations. On the other hand, as became clear from the RTD, workers on unsteady boundary layer problems have doubts on how to proceed.

Therefore, in my opinion the time has come for considering a better spreading of the total effort spent on unsteady aerodynamics. In stead of having an application oriented approach, we should adopt a problem oriented one emphasizing the following two main problem areas:

- a) Attached flow problems, including related viscous-inviscid interactions
- b) Separated flow problems

This distribution also allows for a better answer to the intriguing question of the usefulness of 2-D investigations for the study of 3-D problems. As long as the flow remains attached, in many cases a reduction from 3-D to 2-D flow is possible without violating in essence the physics involved. However, since separation seems to be really a 3-D phenomenon, the study of separated 2-D flows is becoming rather academic.

Also the question of the influence of Reynolds number on unsteady aerodynamic phenomena can be handled better if the proposed division is used. For attached flow we might think of some kind of extrapolation from model test values to free flight. When flow separation is involved Ericsson and Reding²⁵ consider it as impossible to simulate full scale unsteady aerodynamics in dynamic tests at subscale Reynolds numbers.

A further point concerns the position of unsteady aerodynamics with regard to the AGARD Panels. Prior to

this Symposium, aeroelastic problems and related unsteady aerodynamics have been handled by the SMP. This has worked well, since linearized unsteady aerodynamics may be isolated almost completely from steady aerodynamics. A great advantage of handling unsteady aerodynamic problems in the SMP was the direct contact between the people developing the tools and those applying them to aeroelastic problems. However, in problem areas where we need a nonlinear aerodynamic approach, e.g. in the transonic speed regime, the steady flow field influences strongly the unsteady aerodynamic loading. Then the tools can be developed better by aerodynamicists with a good knowledge of steady aerodynamics. In some cases, e.g. time dependent calculation methods, the tools are even suitable for both problem areas. So a close liaison with the FDP becomes necessary. At the same time the connection between unsteady aerodynamics and aeroelasticity should remain strong to avoid the unwanted situation that the aerodynamic tools developed are not adapted to the requirements of the aeroelasticians. For this reason, though the Programme Committee had foreseen some cross-coupling 27, 31, AGARD should promote a prosperous collaboration between SMP and FDP concerning the interdisciplinary topic called unsteady aerodynamics.

4 CONCLUSIONS AND RECOMMENDATIONS

This symposium clearly demonstrated that unsteady aerodynamics covers a wide variety of research topics that may have quite different stages of development.

A satisfactory situation exists for the subsonic and the supersonic speed regimes as long as the flow remains attached. In that case tools are available for determining the aeroelastic behaviour of complete aircraft with external stores. Prediction methods for calculating on a routine basis arbitrary (small) motions are being developed. In general it can be concluded that computational fluid dynamics offers good possibilities for further progress in the near future.

In unsteady transonic aerodynamics the physical understanding has been improved considerably and for 2-D inviscid flow prediction methods show promising results at least in a qualitative way. For 3-D wings instructive elements for an improved engineering type of approach were shown. It has become clear that a strong need exists for boundary layer calculation methods suitable for inclusion in the existing prediction methods.

In experiments on harmonically oscillating models, more attention should be given to the influence of the tunnel walls on the results; especially in the case of 2-D flow which is subject to a higher blockage ratio. A better understanding of the off-design characteristics of advanced wings with supercritical properties e.g. buffeting is urgently needed. Unfortunately this subject was only touched upon in a very few contributions. As buffet boundaries may affect directly the flight envelope of a new design, more attention should be paid to it in the future.

With respect to the study of attached and separated turbulent boundary layers the need for accurate detailed experimental data with well determined initial conditions emerged during the Symposium.

The question of the influence of Reynolds number in unsteady aerodynamic problems is still unresolved. Transonic facilities for dynamic-testing at high or full scale Reynolds numbers are urgently needed to improve understanding.

A lack of communication and collaboration is observed between the people dealing with fixed wing aircraft and those working on helicopter problems. It is recommended that consideration be given to a more problem-oriented approach which makes a distinction between attached flow and separated flow problems. This may provide a better basis for a more appropriate distribution of the total effort spent in unsteady aerodynamics than the application oriented approach followed so far.

The sessions on unsteady flows associated with rotors, cascades and turbo machinery got too little attention. It seems worthwhile to consider a separate specialists meeting for such special fields of application in the future.

Finally since unsteady aerodynamics is a field of interest of both the SMP and the FDP, close co-operation between these two AGARD Panels concerning this topic should be assured.

5 REFERENCES - CONFERENCE PAPERS

Session I - Unsteady subsonic and supersonic flow

1. Ahley, H., Unsteady subsonic and supersonic inviscid flow
2. Kandil, O.A., Atta, E.H. and Nayfeh, A.H. Three dimensional steady and unsteady asymmetric flow past wings of arbitrary planforms
3. Morino, L. and Tseng, K., Steady, oscillatory and unsteady, subsonic and supersonic aerodynamics (SOUSSA) for complex aircraft configurations
4. Patel, M.H., Force measurements on finite wings in oscillatory vertical gusts
5. Geissler, W., Calculation of unsteady airloads on oscillating three-dimensional wings and bodies
6. Das, A. Some basic and new aspects on the disturbance fields of unsteady singularities in uniform motion
7. Bosch, H., Interfering airfoils in two-dimensional unsteady incompressible flow
8. Grenon, R. and Thers, J., Etude d'un profil supercritique avec gouverne oscillante en écoulement subsonique et transsonique
9. Nunen, J.W.G. van, Roos, R. and Meijer, J.J., Investigation of the unsteady airloads of wing-store configurations in subsonic flow

Session II Unsteady transonic flow

10. Tjrdeman, H., Review paper for session II
11. Seebass, A.R., Yu, N.J. and Fung, K.Y., Unsteady transonic flow computations
12. Liu, D.D. and Winther, B.A., Towards a mixed function approach for unsteady transonic flow analysis
13. Sajben, M., Kroutil, J.C. and Chen, C.P., Unsteady transonic flow in a two-dimensional diffuser
14. Ballhaus, W., Goorjian, P. and Yoshihara, H., Unsteady force and moment alleviation in transonic flow
15. Vaucheret, X., Influence du niveau de bruit des souffleries transsoniques sur les caractéristiques aérodynamiques des maquettes

Session III - Unsteady non-separated and separated boundary layers

16. Telionis, D.P., Unsteady boundary layers, separated and attached
17. Cousteix, J., Houdeville, R. and Desopper, A., Résultats expérimentaux et méthodes de calcul relatifs aux couches limites turbulentes en écoulement instationnaire
18. Nash, J.F. and Scruggs, R.M., Unsteady boundary layers with reversal and separation
19. Simpson, R.L., Features of unsteady turbulent boundary layers as revealed from experiments
20. Kenison, R.C., An experimental study of the effect of oscillatory flow on the separation region in a turbulent boundary layer

Session IV - Viscous - inviscid interactions, dynamic stall

21. Philippe, J.J., Le décrochage dynamique: un exemple d'interaction forte entre écoulements visqueux et non-visqueux
22. Saxena, L.S., Fejer, A.A. and Morkovin, M.V., Features of unsteady flows over airfoils
23. Mehta, U.B., Dynamic stall of an oscillating airfoil
24. Wu, J.C., Sampath, S. and Sankar, N.L., A numerical study of unsteady viscous flows around airfoils
25. Ericsson, L.E. and Reding, J.P., Scaling problems in dynamic tests of aircraft-like configurations
26. Kinnery, R.B., Two-dimensional viscous-flow past an airfoil in an unsteady airstream
27. Dat, R. and Angelini, J.J., Les difficultés rencontrées par les aéroélasticiens dans le domaine de l'aérodynamique instationnaire
28. Dymet, A. and Gryson, P., Etude d'écoulements turbulents subsoniques et supercritiques par visualisation ultra-rapide
29. Rebont, J., Maresca, C., Favier, D. and Valensi, J., Récollement dynamique sur un profil d'aile en mouvement de tamis influence des paramètres d'oscillation
30. Panaras, A.G., Design criteria for the non-occurrence of high speed unsteady separation about concave bodies
31. Mykytow, W.J. and Olsen, J.J., A resume of AGARD SMP meeting on transonic unsteady aerodynamics

Session V - Unsteady flows associated with rotors, cascades and turbomachinery

32. Byham, G.M. and Beddoes, T.S., The importance of unsteady aerodynamics in rotor calculations
33. Platzter, M.F., Unsteady flows in turbomachines - a review of current developments
34. Fleeter, S. and Riffel, R.E., Aerodynamic phenomena in an oscillating transonic mca airfoil cascade including loading effects
35. Heinemann, H.J. and Bütefisch, K.A., Determination of the vortex shedding frequency of cascades with different trailing edge thickness

RTD Round Table Discussion

REPORT DOCUMENTATION PAGE												
1. Recipient's Reference	2. Originator's Reference AGARD-AR-128	3. Further Reference ISBN 92-835-1300-2	4. Security Classification of Document UNCLASSIFIED									
5. Originator	Advisory Group for Aerospace Research and Development North Atlantic Treaty Organization 7 rue Ancelle, 92200 Neuilly sur Seine, France											
6. Title	TECHNICAL EVALUATION REPORT on the FLUID DYNAMICS PANEL SYMPOSIUM on UNSTEADY AERODYNAMICS											
7. Presented at												
8. Author(s)/Editor(s) H. Bergh	9. Date October 1978											
10. Author's/Editor's Address National Aerospace Laboratory (NLR) Anthony Fokkerweg 2 1059 CM Amsterdam, The Netherlands	11. Pages 8											
12. Distribution Statement	This document is distributed in accordance with AGARD policies and regulations, which are outlined on the Outside Back Cover of all AGARD publications.											
13. Keywords/Descriptors												
<table border="0"> <tr> <td>Unsteady flow</td> <td>Numerical analysis</td> <td>Transonic flow</td> </tr> <tr> <td>Turbulent boundary layer</td> <td>Aeroelasticity</td> <td>Supersonic flow</td> </tr> <tr> <td>Critical flow</td> <td>Stalling</td> <td></td> </tr> </table>				Unsteady flow	Numerical analysis	Transonic flow	Turbulent boundary layer	Aeroelasticity	Supersonic flow	Critical flow	Stalling	
Unsteady flow	Numerical analysis	Transonic flow										
Turbulent boundary layer	Aeroelasticity	Supersonic flow										
Critical flow	Stalling											
14. Abstract												
<p>↙ The Symposium demonstrated the different stages of development in the broad field of unsteady aerodynamics. Satisfactory tools are available for the subsonic and supersonic speed regime with attached flow. Understanding has been improved in unsteady transonic aerodynamics, but the need for high Reynolds number transonic facility capability is evident. Difficulty in correlation of work in fixed wing and helicopter attached/separated flow problems is noted. Unsteady flows associated with rotors, cascades and turbo-machinery require more attention, and the common interests of structural aeroelasticians in unsteady aerodynamics calls for more collaboration with aerodynamicists. ↗</p> <p>The Symposium was held 26-28 September 1977 at the Government Conference Center, Ottawa, Canada. The 35 papers and Round Table Discussion presented at the Symposium are published in AGARD Conference Proceedings CP-227, dated February 1978.</p>												

<p>AGARD Advisory Report No.128 Advisory Group for Aerospace Research and Development, NATO</p> <p>TECHNICAL EVALUATION REPORT on the FLUID DYNAMICS PANEL SYMPOSIUM on UNSTEADY AERODYNAMICS</p> <p>by H.Bergh Published October 1978 8 pages</p> <p>The Symposium demonstrated the different stages of development in the broad field of unsteady aerodynamics. Satisfactory tools are available for the subsonic and supersonic speed regime with attached flow. Understanding has been improved in unsteady transonic aerodynamics, but the need for high Reynolds number</p> <p>P.T.O.</p>	<p>AGARD-AR-128</p> <p>Unsteady flow Turbulent boundary layer Critical flow Numerical analysis Aeroelasticity Stalling Transonic flow Supersonic flow</p>	<p>AGARD Advisory Report No.128 Advisory Group for Aerospace Research and Development, NATO</p> <p>TECHNICAL EVALUATION REPORT on the FLUID DYNAMICS PANEL SYMPOSIUM on UNSTEADY AERODYNAMICS</p> <p>by H.Bergh Published October 1978 8 pages</p> <p>The Symposium demonstrated the different stages of development in the broad field of unsteady aerodynamics. Satisfactory tools are available for the subsonic and supersonic speed regime with attached flow. Understanding has been improved in unsteady transonic aerodynamics, but the need for high Reynolds number</p> <p>P.T.O.</p>	<p>AGARD-AR-128</p> <p>Unsteady flow Turbulent boundary layer Critical flow Numerical analysis Aeroelasticity Stalling Transonic flow Supersonic flow</p>
<p>AGARD Advisory Report No.128 Advisory Group for Aerospace Research and Development, NATO</p> <p>TECHNICAL EVALUATION REPORT on the FLUID DYNAMICS PANEL SYMPOSIUM on UNSTEADY AERODYNAMICS</p> <p>by H.Bergh Published October 1978 8 pages</p> <p>The Symposium demonstrated the different stages of development in the broad field of unsteady aerodynamics. Satisfactory tools are available for the subsonic and supersonic speed regime with attached flow. Understanding has been improved in unsteady transonic aerodynamics, but the need for high Reynolds number</p> <p>P.T.O.</p>	<p>AGARD-AR-128</p> <p>Unsteady flow Turbulent boundary layer Critical flow Numerical analysis Aeroelasticity Stalling Transonic flow Supersonic flow</p>	<p>AGARD Advisory Report No.128 Advisory Group for Aerospace Research and Development, NATO</p> <p>TECHNICAL EVALUATION REPORT on the FLUID DYNAMICS PANEL SYMPOSIUM on UNSTEADY AERODYNAMICS</p> <p>by H.Bergh Published October 1978 8 pages</p> <p>The Symposium demonstrated the different stages of development in the broad field of unsteady aerodynamics. Satisfactory tools are available for the subsonic and supersonic speed regime with attached flow. Understanding has been improved in unsteady transonic aerodynamics, but the need for high Reynolds number</p> <p>P.T.O.</p>	<p>AGARD-AR-128</p> <p>Unsteady flow Turbulent boundary layer Critical flow Numerical analysis Aeroelasticity Stalling Transonic flow Supersonic flow</p>

<p>transonic facility capability is evident. Difficulty in correlation of work in fixed wing and helicopter attached/separated flow problems is noted. Unsteady flows associated with rotors, cascades and turbomachinery require more attention, and the common interests of structural aeroelasticians in unsteady aerodynamics calls for more collaboration with aerodynamicists.</p> <p>The Symposium was held 26-28 September 1977 at the Government Conference Center, Ottawa, Canada. The 35 papers and Round Table Discussion presented at the Symposium are published in AGARD Conference Proceedings CP-277, dated February 1978.</p> <p>ISBN 92-835-1300-2</p>	<p>transonic facility capability is evident. Difficulty in correlation of work in fixed wing and helicopter attached/separated flow problems is noted. Unsteady flows associated with rotors, cascades and turbomachinery require more attention, and the common interests of structural aeroelasticians in unsteady aerodynamics calls for more collaboration with aerodynamicists.</p> <p>The Symposium was held 26-28 September 1977 at the Government Conference Center, Ottawa, Canada. The 35 papers and Round Table Discussion presented at the Symposium are published in AGARD Conference Proceedings CP-277, dated February 1978.</p> <p>ISBN 92-835-1300-2</p>
<p>transonic facility capability is evident. Difficulty in correlation of work in fixed wing and helicopter attached/separated flow problems is noted. Unsteady flows associated with rotors, cascades and turbomachinery require more attention, and the common interests of structural aeroelasticians in unsteady aerodynamics calls for more collaboration with aerodynamicists.</p> <p>The Symposium was held 26-28 September 1977 at the Government Conference Center, Ottawa, Canada. The 35 papers and Round Table Discussion presented at the Symposium are published in AGARD Conference Proceedings CP-277, dated February 1978.</p> <p>ISBN 92-835-1300-2</p>	<p>transonic facility capability is evident. Difficulty in correlation of work in fixed wing and helicopter attached/separated flow problems is noted. Unsteady flows associated with rotors, cascades and turbomachinery require more attention, and the common interests of structural aeroelasticians in unsteady aerodynamics calls for more collaboration with aerodynamicists.</p> <p>The Symposium was held 26-28 September 1977 at the Government Conference Center, Ottawa, Canada. The 35 papers and Round Table Discussion presented at the Symposium are published in AGARD Conference Proceedings CP-277, dated February 1978.</p> <p>ISBN 92-835-1300-2</p>